

Øving 6 - Løsningsforslag

Problem 6.26

At the interface, the perpendicular component of \mathbf{B} is continuous (Eq. 6.26), and the parallel component of \mathbf{H} is continuous (Eq. 6.25 with $\mathbf{K}_f = 0$). So $B_1^\perp = B_2^\perp$, $H_1^\parallel = H_2^\parallel$. But $\mathbf{B} = \mu\mathbf{H}$ (Eq. 6.31), so $\frac{1}{\mu_1}B_1^\parallel = \frac{1}{\mu_2}B_2^\parallel$. Now $\tan\theta_1 = B_1^\parallel/B_1^\perp$, and $\tan\theta_2 = B_2^\parallel/B_2^\perp$, so

$$\frac{\tan\theta_2}{\tan\theta_1} = \frac{B_2^\parallel/B_2^\perp}{B_1^\parallel/B_1^\perp} = \frac{B_2^\parallel}{B_1^\parallel} = \frac{\mu_2}{\mu_1}$$

(the same form, though for different reasons, as Eq. 4.68).

Problem 7.7

(a) $\mathcal{E} = -\frac{d\Phi}{dt} = -Bl\frac{dv}{dt} = -Blv$; $\mathcal{E} = IR \Rightarrow I = \frac{Blv}{R}$. (Never mind the minus sign—it just tells you the direction of flow: ($\mathbf{v} \times \mathbf{B}$) is upward, in the bar, so downward through the resistor.)

(b) $F = IlB = \frac{B^2 l^2 v}{R}$, to the left.

(c) $F = ma = m\frac{dv}{dt} = -\frac{B^2 l^2}{R}v \Rightarrow \frac{dv}{dt} = -\left(\frac{B^2 l^2}{Rm}\right)v \Rightarrow v = v_0 e^{-\frac{B^2 l^2}{mR}t}$.

(d) The energy goes into heat in the resistor. The power delivered to resistor is $I^2 R$, so

$$\frac{dW}{dt} = I^2 R = \frac{B^2 l^2 v^2}{R^2} R = \frac{B^2 l^2}{R} v_0^2 e^{-2\alpha t}, \text{ where } \alpha \equiv \frac{B^2 l^2}{mR}; \quad \frac{dW}{dt} = \alpha m v_0^2 e^{-2\alpha t}.$$

The total energy delivered to the resistor is $W = \alpha m v_0^2 \int_0^\infty e^{-2\alpha t} dt = \alpha m v_0^2 \left. \frac{e^{-2\alpha t}}{-2\alpha} \right|_0^\infty = \alpha m v_0^2 \frac{1}{2\alpha} = \frac{1}{2} m v_0^2$. ✓

Problem 7.18

$$\Phi = \int \mathbf{B} \cdot d\mathbf{a}; \quad \mathbf{B} = \frac{\mu_0 I}{2\pi s} \hat{\phi}; \quad \Phi = \frac{\mu_0 I a}{2\pi} \int_a^{2a} \frac{ds}{s} = \frac{\mu_0 I a \ln 2}{2\pi}; \quad \mathcal{E} = I_{\text{loop}} R = \frac{dQ}{dt} R = -\frac{d\Phi}{dt} = -\frac{\mu_0 a \ln 2}{2\pi} \frac{dI}{dt}$$

$$dQ = -\frac{\mu_0 a \ln 2}{2\pi R} dI \Rightarrow Q = \frac{I \mu_0 a \ln 2}{2\pi R}$$

The field of the wire, at the square loop, is out of the page, and decreasing, so the field of the induced current must point out of page, within the loop, and hence the induced current flows counterclockwise.

